



Dimensions (approx.)

| | |
|----------------------|----------------|
| Chain width: | 8,80 ± 0,15 mm |
| Chain thickness: | 3,9 mm |
| Single tape widths: | 17 – 22 mm |
| Length of tape ends: | top: 19±3 mm |

Features

| |
|---|
| Woven polyester tape; |
| Slider body out of nylon + fiber glass, puller and cap out of POM |
| Spring and prong - stainless steel & bronze only for auto-lock slider |
| Moulded components made of POM (PolyOxyMethylene) |

TP P80 OE



Quality

| | |
|---------------------------------|--------------|
| Lateral strength | > 500 N |
| Operating force | < 6 N |
| Reciprocation test (durability) | > 500 cycles |
| Pull off strength of puller | > 250 N |
| Slider locking strength | > 25 N |
| Slider over top stops | > 150 N |
| Lateral strength of open end | > 200 N |
| Box pull off strength | > 160 N |

(The quality data represent minimum performance levels)

Main uses

| |
|------------------------|
| Marine equipment |
| Boat covers |
| Life vests and jackets |
| Buoyancy aid |
| Diving vests |
| Military goods |
| Outdoor goods |
| Restaurant extensions |
| Hot houses |
| Tents |
| Awnings |
| Technical applications |

Fastness

| | | Change | Staining |
|---------------|---------------|--------|----------|
| Washing 60° C | (ISO 105-C06) | 4 | 4 |
| Water | (ISO 105-E01) | 4 | 4 |
| Dry-cleaning | (ISO 105-D01) | 4 | 3...4 |
| Light | (ISO 105-B02) | 5 | |
| Rubbing wet | (ISO 105-X12) | | 3... 4 |
| Rubbing dry | (ISO 105-X12) | | 4 |

(These fastness grades represent minimum performance levels and, in practice, the majority of shades will exceed these levels)

Standards

| | |
|----------------------|---|
| EN 16732 – class D | CPSIA HR4040; |
| BS 3084:2006; | F963; |
| DIN 3416 – 19; | EN71; |
| Oeko-Tex 100 Class 1 | QM System according BS EN ISO 9001:2008 |